

PROTECTION

# DEMINING HELMET WITH VISOR DHV6.4

Demining helmet against the blast  
of anti-personnel landmines



# DEMINING HELMET WITH VISOR DHV6.4

## Demining helmet against the blast of anti-personnel landmines

The Demining Helmet DHV6.4 offers a high protection thanks to the combination of a ballistic PASGT helmet and the strong 6.4 mm (0.25 in) retrofit face shield (visor). The ballistic PASGT helmet offers a protection level of  $v_{50} = 670$  m/s (2198 ft/s) according to STANAG 2920. The visor offers a protection level of  $v_{50} = 250$  m/s (820 ft/s) according to STANAG 2920 and exceeds the requirements of IMAS 10.30. The visor can be easily removed and replaced. It protects against the blast of anti-personnel landmines.

The ballistic PASGT Helmet is a general duties helmet suitable for military and police tactical use. The ballistic PASGT helmet is constructed from para-aramid material. It provides lightweight but still very robust protection from ballistic and fragmentation projectiles and other low energy threats.

The latest harness design offers a stable and comfortable fit with individual adjustment capability. This harness is anchored to the shell with ballistic resistant bolts. The harness can be easily removed for cleaning or replacement.

- ✓ High protection with the combination of a ballistic PASGT helmet and a 6.4 mm (0.25 in) removable visor
- ✓ Lightweight and durable
- ✓ Comfortable to wear
- ✓ Harness using 3-point links and quick release catch
- ✓ Excellent suspension system



Black

Coyote brown

Dark blue

Olive

# DATA SHEET

## Demining Helmet with Visor DHV6.4

### TECHNICAL DATA

<b>Article number</b>	S – 1020164-10 M – 1020164-11 L – 1020164-12 XL – 1020164-13
<b>Available sizes and weight</b>	S (50 cm – 56 cm / 19 in – 22 in) – approx. 2.15 kg (4.74 lbs) M (54 cm – 59 cm / 21 in – 23 in) – approx. 2.15 kg (4.74 lbs) L (57 cm – 64 cm / 22 in – 25 in) – approx. 2.20 kg (4.85 lbs) XL (61 cm – 66 cm / 24 in – 26 in) – approx. 2.35 kg (5.18 lbs)
<b>Colors</b>	Black, dark blue, olive, coyote brown
<b>Protection level visor</b>	v50 = 250 m/s (820 ft/s) according to STANAG 2920, exceeds the requirements of IMAS 10.30
<b>Protection level helmet</b>	v50 = 670 m/s (2198 ft/s) according to STANAG 2920, IIIA according to NIJ
<b>Length of visor</b>	Approx. 20 cm, ± 3 mm, (7.87 in, ± 0.12 in)
<b>Warranty</b>	12 months against labor faults
<b>Warranty ballistic material</b>	5 years

