

M8Xi IFS

DMR scope with 34 mm tube increases strength and reliability and provides greater elevation and windage adjustments.



BLACK


Dimensions (approx.)*
281 mm (11 in.) length
900 g (31.7 oz.) weight

Magnification	Eye Relief	Diopter Adjustment	Parallax Adjustment	Elevation Range @ 100 m	Windage Range @ 100 m	Wind/Elevation Click Value
1 - 8x	87 mm (3.4 in.)	-2 to +2 dpt	fixed at 100 m	± 135 cm / ± 13.5 mils	± 60 cm / ± 6.0 mils	1 cm (0.1 mRad)
Objective Lens	Tube diameter	Field of View at 100 m	Operating Temperature	Water-Pressure Proof	Nitrogen Filling	Battery Type / Life
24 mm (0.9 in.)	34 mm (1.3 in.)	34.2 - 4.8 m	-40°C / +49°C (-40°F / +120°F)	20 m (66 ft.)	yes	1 x CR2032

STEINER 
Nothing Escapes You

IFS - Intelligent Firing Solution

- **BUILT IN BALLISTIC CALCULATOR AND SENSOR SUITE** for real time determination of bullets point of impact
- **DISPLAY OF FIRING SOLUTION** into the Field of View, providing a sophisticated user interactivity
- **DISPLAY AND USER INTERFACE** customizable to user needs
- **BLUETOOTH CONNECTIVITY** to other devices (e.g. Smart Phones) for easy set-up of IFS
- **SHORT OVERALL LENGTH** for clip-on devices (e.g. thermal imaging or night vision devices)
- **PRECISE WINDAGE/ELEVATION ADJUSTMENT** is easy and accurate for repeated accuracy, with tactile click-by-click feedback you can hear and feel
- **OPTIMIZED TUBE AND KNOB CONFIGURATION** for more mounting options and optimum performance with different rifles and added equipment
- **WATERPROOF/FOGPROOF** durable construction you can trust to stand up to any cold or wet condition
- **SHOCKPROOF** and rugged enough to withstand impact testing to 900 Gs on all optical and electronic components



DMR8i RETICLE SUBTENSIONS